

Quick Installation

Solid State

NEMA Load Switch

NEMA Flashers

4 Pin Plug-In Flasher



Model 204 – NEMA Flasher

10 amp @ 120 VAC
 LEDs across load
 60 or 120 FPM ±.1% (Front panel switch)
 -45°C to +85°C
 Zero voltage on, zero current off
 DV/DT 200v/μ sec.
 Built in snubbers



Model 200 – NEMA Load Switch

3 circuit 10 amp @ 120 VAC
 LEDs across load, input or both (R,Y & G)
 60 FPM ± .1%
 -45°C to +85°C
 7.5 KV OPTO isolation
 Zero voltage on, zero current off
 Leakage current: 6ma max.
 24 VDC control @ 10 MA max.
 True negative logic
 Reverse polarity protection

TF-3 & TF-4 – 4 Pin Plug-In Flashers

10 amp @ 120 VAC
 60 or 120 FPM ± .1% (internal switch)
 -45°C to +85°C
 Zero voltage on, zero current off
 DV/DT 200 v/μ sec.
 Built in snubbers



Electro Systems Inc.
 #8- 415 Dunedin Street
 Victoria, BC, Canada V8T 5G8
 Tel: 250.385.0911
 toll free: 1.800.668.2254
 Fax: 250.385.0733
 toll free: 1.800.661.4977